

ITEM CODE White	RATED CURRENT	RATED VOLTAGE	ITEM DESCRIPTION
100-0110	10AX	250V~	1Gang 1Way Switch
100-0210	10AX	250V~	1Gang 2Way Switch
100-0120	10AX	250V~	2Gang 1Way Switch
100-0220	10AX	250V~	2Gang 2Way Switch
100-0130	10AX	250V~	3Gang 1Way Switch
100-0230	10AX	250V~	3Gang 2Way Switch
100-0140	10AX	250V~	4Gang 1Way Switch
100-0240	10AX	250V~	4Gang 2Way Switch
100-0150	10AX	250V~	5Gang 1Way Switch
100-0250	10AX	250V~	5Gang 2Way Switch

APPLICATIONS

Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Method of Application	: Flush type
Method of Connecting Cables	: Rewireable
Type of Terminals	: Screw type
Method of Installation	: Fixed
Mounting Center Distance	: 60.3mm
Recommended Mounting Box Depth	: 35mm
Warranty Period	: Lifetime warranty*
Standard Complied	: IEC 60669 BS EN 60669 IS 3854 SLS 1000
Materials	: Plastics: Polycarbonate & Nylon (Flame Retardant) Metal Parts: Brass & Copper Contacts: Pure Silver & Silver Cadmium

