

ALPHA

1 POLE MCB					
ITEM CODE	RATED CURRENT	NO. POLES	TYPE	RATED VOLTAGE	RATED SHORT CIRCUIT CAPACITY (Icn)
470-1002	6A	1	C	230/400V	6kA
470-1003	10A	1	C	230/400V	6kA
470-1004	16A	1	C	230/400V	6kA
470-1005	20A	1	C	230/400V	6kA
470-1007	32A	1	C	230/400V	6kA

APPLICATIONS

Industrial/Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Connection	: Screw type terminals
Method of Installation	: Mounting on 35mm DIN rail
Warranty Period	: Five years warranty*
Standard Complied	: IEC 60898-1 / SLS 1175
Certification	: SLS
Protection	: Against overload and short circuit
Protected Poles	: All poles protected
Rated Voltage	: 1 pole - 230/400VAC
Rated Frequency	: 50/60Hz
Rated Current	: 6, 10, 16, 20, 32 A
Type of Trip	: Thermal/ Magnetic release
Rated Service Short Circuit Capacity(Ics)	: 6kA
Temperature Limit	: -5 °C to +40 °C
Instantaneous Tripping Characteristics	: Type C
Degree of Protection	: IP20
Rated Impulse withstand Voltage(Uimp)	: 4kV

