10kA

4 POLE MCB					
ITEM CODE	RATED CURRENT	NO.POLES	TYPE	RATED VOLTAGE	RATED SHORT CIRCUIT CAPACITY (Icn)
510-1029	6A	4	C	415V	10kA
510-1030	10A	4	C	415V	10kA
510-1031	16A	4	C	415V	10kA
510-1032	20A	4	C	415V	10kA
510-1033	25A	4	C	415V	10kA
510-1034	32A	4	C	415V	10kA
510-1035	40A	4	C	415V	10kA
510-1037	63A	4	C	415V	10kA

APPLICATIONS

Industrial/Residential/Hotel/General Purpose

PRODUCT SPECIFICATIONS

Connection	:	Screw type terminals
Method of Installation	:	Mounting on 35mm DIN rail
Warranty Period	:	Lifetime warranty*
Standard Complied	:	IEC 60898-1 / SLS 1175
Certification	:	SLS, ISI
Protection	:	Against overload and short circuit
Protected Poles	:	All poles protected
Rated Voltage	:	4 pole - 415VAC
Rated Frequency	:	50/60Hz
Rated Current	:	6, 10, 16, 20, 25, 32, 40, 63 A
Type of Trip	:	Thermal/ Magnetic release
Rated Service Short Circuit Capacity(Ics)	:	7.5kA
Temperature Limit	:	-5 ºC to +40 ºC
Instantaneous Tripping Characteristics	:	Type C
Degree of Protection	:	IP20
Rated Impulse withstand Voltage(Uimp)	:	4kV





© 2019 OREL CORPORATION (PVT) LTD. All rights reserved.

*Terms & Conditions Applied